

65 SERIES



SPECIFICATIONS	65M1-A1	65M1-A1 TC
TYPE OF VEHICLE (4x4)	Subcompact Truck or SUV (ex. Jeep Wrangler, Geo Tracker)	Specifically Designed to fit Bobcat Toolcat
RECOMMENDED MAX GVW	6,500 lbs	Bobcat Toolcat
RECOMMENDED MAX SPEED	40 mph	11.5 mph
FRAME CONSTRUCTION	Steel	
STEERING ASSIST (ADDS 25 LBS)	N/A	N/A
ASSEMBLY WEIGHT	289 lbs	310 lbs
INTERNAL SUSPENSION	Concentric Pivot	
TRACK TREAD WIDTH	15"	
TRACK TREAD STYLE	All-Terrain, Self-Cleaning	
TRACK MATERIAL	Rubber with Internal Composite, Cord	
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°	
AXLE HEIGHT	19.8"	
GROUND CONTACT LENGTH	(Hard Surface) 30.8" / (Soft Surface) 45"	
GROUND CONTACT SURFACE AREA	462 sq in min / 675 sq in max	
SPROCKET DIAMETER (STANDARD)	16.5"	
WHEEL TYPE	(4) 8" x 1.5" and (4) 12" x 1.5" HD Extra Seals	
ROAD WHEEL COUNT	8, 2 rows	
WHEEL MATERIAL	UMHW / Rubber	
PAINT COLOR	Silver Metallic (Standard, other colors available)	White & Orange (Standard, other colors available)

* ALL SPECS ARE PER CORNER

MODELS IN SERIES: 65M1-A1, 65M1-A1 TC



KUBOTA RTV900 ON 65M1-A1 TC



JEEP WRANGLER ON 65M1-A1



BOBCAT TOOLCAT 5600 ON 65M1-A1 TC

MATTRACKS
RUBBER TRACK CONVERSIONS

ALL SPECIFICATIONS ARE APPROXIMATE AND WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION

202 Cleveland Ave E · PO Box 214 · Karlstad, MN 56732 · 877.436.7800 · mattracks.com